





# 100MNDTDiBF

## **Threshold for Bifold Doors**



Allows door tracks to be drained while having internal and external floor surfaces with no step down.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.



Channel Material Stainless Steel

Steel Grade 316

Code 100MNDTDiBF

# Track Track Width Track Overall Depth Minimum 52mm Maximum 100mm

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions.

#### SPECIFICATIONS + DIMENSIONS

Channel Width 105mm

**Channel Depth** 52mm - Adjustable **Length(s)** As Required

Outlet Size N/.

#### STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

### PRODUCT APPLICATIONS

Aged / Health Care Drainage Balcony Drainage Commercial Drainage Multi-Residential Drainage Special Needs Drainage Threshold Drainage

Suspended Slab Drainage







Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 18/09/2025 (please check for updates)