

ARCHITECTURAL

GRATES + DRAINS

Code 200Custom-316-C

Category Custom Made

Recessed Channel

208mm

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts

40mm Minimum

200mm Maximum

Grate Style CR

Steel Grade 316

dimensions

Range Custom Fabrication



200Custom-316-C **Linear Drain**

316 stainless steel 200mm wide grate and custom channel depth.

Depth between 42mm and 210mm.

Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish.

Suits Load Class C.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency.

SPECIFICATIONS + DIMENSIONS

Channel Width **Channel Depth** Length(s) **Outlet Size**

210mm 42mm - 210mm As Required DN40, DN50, DN65, DN80, DN100

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Bathroom Drainage Aged / Health Care Drainage **Balcony Drainage Commercial Drainage** Courtyard / Patio Drainage **Driveway Drainage**

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown Downloaded 18/09/2025 (please check for updates)



Visit **stormtech.com.au** for tools + inspiration.

longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on