



# 225Custom-304-B

## **Linear Drain**



Available with a 5mm wire x 5mm gap and 5mm wire x 5mm gap Grate Grip slip resistant dimple finish. Custom depth from 42mm to 235mm.

Suits Load Class B.

For site specific needs or unusual situations, choose from our Custom Fabrication range.

Stormtech can customise any drainage requirements to achieve maximum efficiency



Channel Material Stainless Steel

Code 225Custom-304-B

Range Custom Fabrication

Steel Grade 304

Grate Style CR


Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on dimensions

#### SPECIFICATIONS + DIMENSIONS

**Channel Width** 235mm **Channel Depth** 42mm - 235mm Length(s) As Required

**Outlet Size** DN40, DN50, DN65, DN80, DN100

#### STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

### **PRODUCT APPLICATIONS**

Bathroom Drainage Aged / Health Care Drainage **Balcony Drainage** Commercial Drainage Courtyard / Patio Drainage **Driveway Drainage** 

Pool and Spa Area Drainage Hospitality Drainage Paved Area Drainage Shower Drainage Multi-Residential Drainage Special Needs Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 18/09/2025 (please check for updates)





